





		<b>[NEW] Micro Slitter</b>	<b>Multi-Purpose Large Slitter</b>	<b>Large Slitter</b>	<b>Multi-Purpose Slitter</b>	<b>Optical Slitter</b>
						
<b>Feature</b>		Available for narrow and thicker diameter films. Blade unit is also capable of being customized.	A 40mm friction shaft enables to slit into multiple splits. As it is less digital handling, various condition settings are available so that mainly used for development and preproduction.	It is mainly used for optical purposes as the cleanliness improves up to class 100. Shaft winding and up to two splits are available.	A 50mm friction shaft enables to slit into multiple splits. Register conditions by touch panel is available.	Since all rollers function as control of drive, extremely damage free and high quality of slitting is available. Also, all windings are controlled by a single motor which enables high grade and steady process. Four types of feeding and our original combination of blades bring the best cut edge for your need. Up to three splits are available.
<b>Environment</b>	<b>Cleanliness</b>	General Environment	Comparable to Class 10000	Comparable to Class 1000	Comparable to Class 5000	Comparable to Class 5000
	<b>Lighting</b>	Bright Room	Bright and Dark Room Yellow Light	Bright and Dark Room Yellow Light	Bright Room	Bright Room
<b>Raw Materials</b>	<b>Thickness</b>	5 $\mu$ m~500 $\mu$ m (reference value)	5 $\mu$ m~1000 $\mu$ m (actual value)	40 $\mu$ m~350 $\mu$ m (actual value)	8 $\mu$ m~500 $\mu$ m (actual value)	16 $\mu$ m~500 $\mu$ m (actual value)
	<b>Width</b>	~640mm	100mm~1580mm	300mm~1580mm	100mm~1580mm	500mm~1650mm
	<b>Diameter</b>	φ800	φ1000	φ1000	φ1000	φ1000
	<b>Weight</b>	500kg	1 t	1 t	1 t	1 t
	<b>Core</b>	3in	3in, 6in, Others	3in, 6in, Others	3in, 6in, Others	3in, 6in, Others
<b>Products</b>	<b>Thickness</b>	5 $\mu$ m~500 $\mu$ m (reference value)	5 $\mu$ m~1000 $\mu$ m (actual value) ※Please ask for over 500 $\mu$	40 $\mu$ m~350 $\mu$ m (actual value)	8 $\mu$ m~500 $\mu$ m (actual value)	16 $\mu$ m~500 $\mu$ m (actual value)
	<b>Width</b>	8mm~640mm	40mm~1560mm	500mm~1500mm (up to two splits)	50~1560mm	500mm~1600mm (up to three splits)
	<b>Diameter</b>	φ650	φ650	φ600	φ500	φ800
	<b>Weight</b>	200kg	500kg	500kg	500kg	1 t
	<b>Core</b>	3in	3 in, 6 in	3 in, 6 in	3 in, 6 in	3 in, 6 in, Others